

### 75-90 kW

75-90 kW

| Code              | Power         | Air outflow rate<br>(min. / max.) |              | Max<br>pressure** |        | Sound<br>level | Air<br>outlet | Net<br>weight | Net<br>dimensions |                    |
|-------------------|---------------|-----------------------------------|--------------|-------------------|--------|----------------|---------------|---------------|-------------------|--------------------|
|                   | kW            | m³/min.                           | c.f.m.       | bar               | p.s.i. | dB(A)          | DN            | kg            | L x P x H (mm)    |                    |
| 75 kW             |               |                                   |              |                   |        |                |               |               |                   |                    |
| K-MAX TS 75-07 VS | V60ZB97FNMA87 | 75                                | 5,48 / 16,60 | 194 / 586         | 7      | 101            | 73            | DN50          | 3260              | 3000 x 2000 x 2200 |
| K-MAX TS 75-08 VS |               | 75                                | 5,19 / 15,70 | 183 / 554         | 8      | 116            | 73            | DN50          | 3260              | 3000 x 2000 x 2200 |
| K-MAX TS 75-10 VS |               | 75                                | 4,65 / 14,10 | 164 / 498         | 10     | 145            | 73            | DN50          | 3260              | 3000 x 2000 x 2200 |
| 90 kW             |               |                                   |              |                   |        |                |               |               |                   |                    |
| K-MAX TS 90-07 VS | V60ZE97FNMA87 | 90                                | 6,34 / 19,20 | 224 / 678         | 7      | 101            | 73            | DN50          | 3500              | 3000 x 2000 x 2200 |
| K-MAX TS 90-08 VS |               | 90                                | 6,30 / 19,10 | 222 / 675         | 8      | 116            | 73            | DN50          | 3500              | 3000 x 2000 x 2200 |
| K-MAX TS 90-10 VS |               | 90                                | 5,61 / 17,00 | 198 / 600         | 10     | 145            | 73            | DN50          | 3500              | 3000 x 2000 x 2200 |

### 110-160 kW

110-160 kW

| Code               | Power         | Air outflow rate<br>(min. / max.) |               | Max<br>pressure** |        | Sound<br>level | Air<br>outlet | Net<br>weight | Net<br>dimensions |                    |
|--------------------|---------------|-----------------------------------|---------------|-------------------|--------|----------------|---------------|---------------|-------------------|--------------------|
|                    | kW            | m³/min.                           | c.f.m.        | bar               | p.s.i. | dB(A)          | DN            | kg            | L x P x H (mm)    |                    |
| 110 kW             |               |                                   |               |                   |        |                |               |               |                   |                    |
| K-MAX TS 110-07 VS | V60ZH97FNMA87 | 110                               | 8,22 / 24,90  | 290 / 879         | 7      | 101            | 76            | DN80          | 5300              | 3600 x 2000 x 2250 |
| K-MAX TS 110-08 VS |               | 110                               | 7,43 / 22,52  | 262 / 795         | 8      | 116            | 76            | DN80          | 5300              | 3600 x 2000 x 2250 |
| K-MAX TS 110-10 VS |               | 110                               | 6,99 / 21,19  | 247 / 748         | 10     | 145            | 76            | DN80          | 5300              | 3600 x 2000 x 2250 |
| 132 kW             |               |                                   |               |                   |        |                |               |               |                   |                    |
| K-MAX TS 132-07 VS | V60ZL97FNMA87 | 132                               | 9,24 / 28,00  | 326 / 989         | 7      | 101            | 76            | DN80          | 5500              | 3600 x 2000 x 2250 |
| K-MAX TS 132-08 VS |               | 132                               | 8,91 / 27,00  | 315 / 953         | 8      | 116            | 76            | DN80          | 5500              | 3600 x 2000 x 2250 |
| K-MAX TS 132-10 VS | V60ZM97FNMA87 | 132                               | 8,56 / 25,94  | 302 / 916         | 10     | 145            | 76            | DN80          | 5730              | 3600 x 2000 x 2250 |
| 160 kW             |               |                                   |               |                   |        |                |               |               |                   |                    |
| K-MAX TS 160-07 VS | V60ZP97FNMA87 | 160                               | 11,43 / 34,65 | 404 / 1224        | 7      | 101            | 76            | DN80          | 5730              | 3600 x 2000 x 2250 |
| K-MAX TS 160-08 VS |               | 160                               | 10,89 / 33,00 | 385 / 1165        | 8      | 116            | 76            | DN80          | 5730              | 3600 x 2000 x 2250 |
| K-MAX TS 160-10 VS | V60ZQ97FNMA87 | 160                               | 9,90 / 30,00  | 350 / 1059        | 10     | 145            | 76            | DN80          | 5890              | 3600 x 2000 x 2250 |

### 200-315 kW

200-315 kW

| Code               | Power         | Air outflow rate<br>(min. / max.) |               | Max<br>pressure** |        | Sound<br>level | Air<br>outlet | Net<br>weight | Net<br>dimensions |                    |
|--------------------|---------------|-----------------------------------|---------------|-------------------|--------|----------------|---------------|---------------|-------------------|--------------------|
|                    | kW            | m³/min.                           | c.f.m.        | bar               | p.s.i. | dB(A)          | DN            | kg            | L x P x H (mm)    |                    |
| 200 kW             |               |                                   |               |                   |        |                |               |               |                   |                    |
| K-MAX TS 200-07 VS | V60ZS97FNMA87 | 200                               | 14,35 / 43,50 | 507 / 1536        | 7      | 101            | 79            | DN100         | 7310              | 4350 x 2250 x 2450 |
| K-MAX TS 200-08 VS |               | 200                               | 13,43 / 40,70 | 474 / 1437        | 8      | 116            | 79            | DN100         | 7310              | 4350 x 2250 x 2450 |
| K-MAX TS 200-10 VS | V60ZT97FNMA87 | 200                               | 12,21 / 37,00 | 431 / 1307        | 10     | 145            | 79            | DN100         | 7400              | 4350 x 2250 x 2450 |
| 250 kW             |               |                                   |               |                   |        |                |               |               |                   |                    |
| K-MAX TS 250-07 VS | V60ZV97FNMA87 | 250                               | 17,65 / 53,50 | 623 / 1889        | 7      | 101            | 79            | DN100         | 8440              | 4350 x 2250 x 2450 |
| K-MAX TS 250-08 VS |               | 250                               | 16,85 / 51,05 | 595 / 1803        | 8      | 116            | 79            | DN100         | 8440              | 4350 x 2250 x 2450 |
| K-MAX TS 250-10 VS |               | 250                               | 14,88 / 45,10 | 525 / 1593        | 10     | 145            | 79            | DN100         | 8440              | 4350 x 2250 x 2450 |
| 315 kW             |               |                                   |               |                   |        |                |               |               |                   |                    |
| K-MAX TS 315-07 VS | V60ZY97FNMA87 | 315                               | 20,79 / 63,00 | 734 / 2225        | 7      | 101            | 79            | DN100         | 8500              | 4350 x 2250 x 2450 |
| K-MAX TS 315-08 VS |               | 315                               | 20,29 / 61,50 | 717 / 2172        | 8      | 116            | 79            | DN100         | 8500              | 4350 x 2250 x 2450 |
| K-MAX TS 315-10 VS |               | 315                               | 18,48 / 56,00 | 653 / 1978        | 10     | 145            | 79            | DN100         | 8500              | 4350 x 2250 x 2450 |

\*\* Max. pressure up to 13 bar on request.

The data and results were measured in accordance with standard ISO 1217.

The sound level was measured in accordance with ISO 2151, with a tolerance of ± 3 dB(A).