



| Code | Product | Compressor | | AIR ** | | | MAX | | dB(A) | BSP | Weight | | L x W x H (cm) |
|----------------------------------|------------------|------------|----|-------------|-------------------|----------|-----|-----|-------|------|--------|-----|----------------|
| | | kW | HP | l/min. | m ³ /h | c.f.m. | bar | psi | | | kg | Lbs | |
| FLOOR MOUNTED | | | | | | | | | | | | | |
| V60QA92FNM760 | PLUS 18.5-08 | 18.5 | 25 | 2800 | 168 | 99 | 8 | 116 | 66 | 3/4" | 350 | 774 | 135 x 80 x 113 |
| V60QB92FNM760 | PLUS 18.5-10 | 18.5 | 25 | 2500 | 150 | 88 | 10 | 145 | 66 | 3/4" | 350 | 774 | 135 x 80 x 113 |
| V60QC92FNM760 | PLUS 18.5-13 | 18.5 | 25 | 2150 | 129 | 76 | 13 | 188 | 66 | 3/4" | 350 | 774 | 135 x 80 x 113 |
| V60QD92FNM760 | PLUS 22-08 | 22 | 30 | 3350 | 201 | 118 | 8 | 116 | 68 | 3/4" | 380 | 840 | 135 x 80 x 113 |
| V60QE92FNM760 | PLUS 22-10 | 22 | 30 | 3000 | 180 | 106 | 10 | 145 | 68 | 3/4" | 380 | 840 | 135 x 80 x 113 |
| V60QF92FNM760 | PLUS 22-13 | 22 | 30 | 2400 | 144 | 85 | 13 | 188 | 68 | 3/4" | 380 | 840 | 135 x 80 x 113 |
| WITH DRYER | | | | | | | | | | | | | |
| V60QA92FNM860 | PLUS 18.5-08 ES | 18.5 | 25 | 2800 | 168 | 99 | 8 | 116 | 66 | 3/4" | 400 | 883 | 169 x 80 x 113 |
| V60QB92FNM860 | PLUS 18.5-10 ES | 18.5 | 25 | 2500 | 150 | 88 | 10 | 145 | 66 | 3/4" | 400 | 883 | 169 x 80 x 113 |
| V60QC92FNM860 | PLUS 18.5-13 ES | 18.5 | 25 | 2150 | 129 | 76 | 13 | 188 | 66 | 3/4" | 400 | 883 | 169 x 80 x 113 |
| V60QD92FNM860 | PLUS 22-08 ES | 22 | 30 | 3350 | 201 | 118 | 8 | 116 | 68 | 3/4" | 430 | 949 | 169 x 80 x 113 |
| V60QE92FNM860 | PLUS 22-10 ES | 22 | 30 | 3000 | 180 | 106 | 10 | 145 | 68 | 3/4" | 430 | 949 | 169 x 80 x 113 |
| V60QF92FNM860 | PLUS 22-13 ES | 22 | 30 | 2400 | 144 | 85 | 13 | 188 | 68 | 3/4" | 430 | 949 | 169 x 80 x 113 |
| VARIABLE SPEED | | | | | | | | | | | | | |
| V60QD97FNM760 | PLUS 22-08 VS | 22 | 30 | 3350 / 1350 | 201 / 81 | 118 / 48 | 8 | 116 | 68 | 3/4" | 390 | 861 | 135 x 80 x 113 |
| V60QE97FNM760 | PLUS 22-10 VS | 22 | 30 | 3050 / 1220 | 183 / 73.2 | 108 / 43 | 10 | 145 | 68 | 3/4" | 390 | 861 | 135 x 80 x 113 |
| VARIABLE SPEED WITH DRYER | | | | | | | | | | | | | |
| V60QD97FNM860 | PLUS 22-08 ES VS | 22 | 30 | 3350 / 1350 | 201 / 81 | 118 / 48 | 8 | 116 | 68 | 3/4" | 440 | 971 | 169 x 80 x 113 |
| V60QE97FNM860 | PLUS 22-10 ES VS | 22 | 30 | 3050 / 1220 | 183 / 73.2 | 108 / 43 | 10 | 145 | 68 | 3/4" | 440 | 971 | 169 x 80 x 113 |

Free air delivery as per ISO 1217 Annex C, at 7.5 - 9.5 - 12.5 bar at the compressor outlet. ± 3 dB (A) as PNEUROP/CAGI PN-NTC 2.3.
 ** Variable Speed models: max./min. values.